ROUSH INDUSTRIES INC.

EXECUTIVE ORDER A-344-0013 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR			EXHAUST EMISSION STANDARD CATEGORY	USEFU (mll		IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. iate in-use)	FUEL TYPE	
2010	ARIITO5.4CHA	LDT: 6001-8500# GVW, 5751-	"LEV II" Low Emission Vehicle (LEV II LEV)	ORVR EVAP		EXH EVAP		LPG	
		8500# ALVW		120K			*	}	
No.		SPECIAL FEATURES	EVAPORATIVE		DISPLACEMENT (L)				
1	2TWC, 2	2HO2S(2), SFI, OBD(F)	ARIIR02	40LPG					
•	•	4		5.4					
•		*		•					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2010 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2010 model year vehicles.

BE IT FURTHER RESOLVED: The listed vehicle models are conditionally certified on the manufacturer submitting test data demonstrating compliance of cold temperature CO with the emission standards, "2001 and subsequent model-year cold temperature carbon monoxide exhaust emissions standards for passenger cars, light-duty trucks, and medium-duty vehicles" by May 4, 2009. Failure to submit the test data in the specified time, or failure of the submitted data showing compliance with the listed standards, shall be cause for the Executive Officer to rescind this conditional certification.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of April 2009.

Annette Hebert, Chief

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF AVERAGE [g/ml] CH4 RAF = '			NMOG or	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; If HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram											
CERT	STD	NMOG	NMHC	NMHC STD		(=1000 miles								iii; mg-iisii)	gram
0.045	0.075	CERT	CERT	[g/ml]	CO	CO (g/mi)		NOx [g/mi]		fCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
0.043	0.015	[g/mi]	[g/mi]		CERT	STD	CERT	STE	CE	RT S	TD	CERT	STD	CERT	STD
	@ 50K	0.032	*	0.075	1.0	3.4	0.03	0.08	;	• /	15.	*	*	0.04	0.07
	@ UL	0.052	* [0.090	2.1	4.2	0.05	0.07	, ,	, ,	18.	*	0.01	0.06	0.09
	@ 50°F & 4K	٠	٠	4	•	•	*	•			*	*	*	*	٠
CO [g/mi] @ 20°F & 50K		ř.	1	NMHC+N(comp								NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	*	SFTP	@ * miles	*	*	*	•	*	•	*		*	*	*	•
STD	12.5	SFTP	@ * miles	*	4	*	•	*	+	•	*	*	*	*	ŧ
3-Days Di Evaporative Family (gram			ırnal + Hot s/test) @ l					Running Loss (grams/mile) @ UL.				On-Board Refueling Vapor Recovery (grams/gallon) @ UL			
EV												1			

Evaporative Family	3-Days Diurnal + Hot Soak (grams/test) @ UL			al + Hot Soak est) @ UL		ng Loss nile) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	\$TD	CERT	STD	CERT	STD	CERT	STD	
ARIIR0240LPG	0.85	0.90	0.88	1.15	•	0.05	*	0.15	
•	+	•	•	*	*	*	*	*	
*	•	*	•	*	•	*	* .	•	
•	*	*	• '	*	*	. *	*	•	

^{* =} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; DGI=direct gasoline fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=fuil/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel;

2010 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full In-use; A/E=exh. / evap. Intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		•
ROUSH	F150 4x2 Propane	ARIIR0240LPG	1	5.4	*	*	SFTP	Full
ROUSH	F150 4x4 Propane	ARIIR0240LPG	1	5.4	•	*	SFTP	Full
ROUSH	Mark LT 4x2 Propane	ARIIR0240LPG	1	5.4	•	•	SFTP	Full
ROUSH	Mark LT 4x4 Propane	ARIIR0240LPG	1	. 5.4	*	*	SFTP	Full
ROUSH	F150 STX 4x2 Propane	ARIIR0240LPG	1	5.4	*	*	SFTP	Full